

## RST

### Heat Shrink Termination for LV Cables



Termination kit for 4-core cables

The terminations are designed for 1-, 2-, 3-, 4- and 5-core cables with or without armour. The terminations are also applicable to 3+1, 4+1 and 3+2 cables.

The cable crutch is sealed by a breakout inner coated with adhesive. Heat shrink insulation tubes seal between the cable lug and the bottom of the core insulation. For single core cables only an insulation tube is needed. All materials are resistant to UV and weathering.

#### Selection Table

Voltage	Cores	Cross Section/mm <sup>2</sup>	Kit No.
0.6/1(1.2)kV	1,2,3,4,5	4-6	0.6/1kVRST-4(5,3,2)/(-1)
		10-16	0.6/1kVRST-4(5,3,2)/0
		25-50	0.6/1kVRST-4(5,3,2,1)/1
		70-120	0.6/1kVRST-4(5,3,2,1)/2
		150-240	0.6/1kVRST-4(5,3,2,1)/3
		300-400	0.6/1kVRST-4(5,3,2,1)/4
		500	0.6/1kVRST-4(3,2,1)/5

#### Note:

Solderless earth connection system for armoured cables is available on request.

Lugs and other accessories shall be ordered separately.

Terminations and components for other cable types are available on request.